

UV LASER MARKING SYSTEM MODEL CM 800U



MORE THAN A CENTURY OF GLOBAL MARKING, CODING & PACKAGING SOLUTIONS

UV LASER PRINTER

CM 800U series UV- laser marking system has extremely small focusing spot and minimal processing heat and impact on material. A laser from the CM 800 series is the first choice for customers with high demands on marking quality.

√ For ultra fine marking needs like special material marking, such as food, tobacco, medicine, electronic components, chemicals, building materials, painted metal surface, glass and many other applications √ Easy to operate



CM 800U series UV laser is developed with 355nm UV laser, which is especially suitable for ultra-fine marking, special material marking, such as food, tobacco, medicine, electronic components, chemicals, building materials, painted metal surface, glass and other applications due to its extremely small focusing spot and minimal processing heat and impact on the deformation of the material. It is the first choice for customers with high standard of marking quality.

Non-stop

- ✓No consumables in daily operation and no needs of daily mechanical maintenance procedures will effectively extend the up-time
- ✓Air cooled laser source will maximize machine utilization and reduce the unplanned downtime
- ✓ Fully enclosed maintenance-free optical system and no adjustment required ensures the stability of the entire system

Easy to operate

- ✓ Flexible integrated solution with multiple standard beam transmission options
- √Highly integrated modular design ensures simple and convenient installation and maintenance
- ✓Intuitive touch screen interface, easier to edit information, simple to learn, support a variety of communication methods









High efficiency

- ✓ High-speed digital galvanometer system to ensure high speed and accuracy
- ✓Scientific and accurate vector planning logic to reduce marking period
- ✓Ultra-high-speed makes up to 150,000 marking per hour
- ✓Ultraviolet wave length laser beam makes high speed flying marking on HDPE/LDPE packaging possible

High Quality

- √"Cold processing" with small focal spot and heat effect ensures the minimiation of damage to packaging
- √ Fine and non-erasable marking to help on realization of traceability and anticounterfeiting in the whole product life cycle
- ✓Achievable high-contrast with great visual readability on white HDPE/LDPE packaging

Technical Specifications	
Marking speed	Up to 2,000 characters/second
Line Speed	Up to 200/min
Marking format	Approx.70x70mm²to 220x220mm²
Wave lengths	355nm
Marking format	Standard industrial fonts, Bar codes, Q-R code, Data Matrix, Aztec -code, Han-Xin-code, Graphics, Logos, Symbols etc.
Laser tube	Solid-state UV laser
User interface	Personalized touch control screen
Communication	UDP, TCP/IP and RS232
Integration	Flexible beam delivery options
Electrical requirement	240 VAC (To be noted when ordering), ~50/60 Hz, 1 PH, 0.70 KW / 1.50 KW
Environment	Temperature 5-40°C (41-104°F) Humidity 10%-90%, no condensing
Sealing and safety standards	Cabinet: IP54 standard, Marking Unit: IP54 standard
Weight	Standard unit: approx. 28 kg





www.cyklop-india.com

Cavalier Enterprises
Authorised distributor of Cyklop (India) Pvt. Ltd.

6A/12 Sneh, Sadguru wamanrao pai marg, Abhinav Nagar,Borivali East, Mumbai, Maharashtra, India 400066 Direct Line: +91 22-68843786 Mobile / Whatsapp: +91 9321814744 Email: business@cavalier-enterprises.com



