



CP 19CA

STRAPPING MACHINE

CYKLOP[®]
GLOBAL PACKAGING SOLUTIONS

STRAPPING
WRAPPING
CODING
TAPING

The automatic strapping machine CP 19CA is suitable for strapping various packages or boxes. The machine is able to process PP strap of 9 to 19 mm and has a very simple control panel. The CP 19CA is also mobile because of the swivel wheels. The strapping machine can make up to 30-32 strappings per minute, depending on the set tension, package size and arch size. This makes the CP 19CA ideal as a starter in automatic strapping.

Advantages

- For PP strap of 9 to 19 mm, thickness from 0.6 – 1.0 mm
- Automatic belt insertion and ejection
- Easy operation
- Electronic tension control
- Built-in photo sensor for automatic strapping
- Mobile, equipped with foot pedal
- Various arch sizes available



Technical Specifications

Min. package size	200 x 750 x 500 mm (LxWxH)
Strapping material	Polystrap 9,10,11,12,13,15,19 mm Thickness 0.6 ~ 1.0mm
Strap coil	Core diameter 200 mm Outer diameter 400 mm Width 160 mm
Strap tension	70 - 882 N ~90 Kgs.
Packing Type	Parallel Strapping, Continuous Mode Manual Operation, Ball Switch
Sealing method	Hotseal
Noise	~75 dB(A)
Warm up time	Approximately 1 min
Power	380V, 50/60 Hz 1.0kW 10A 3P
Machine weight	Approximately 220 kg
Machine Dimensions	L1380 x W620 x H1540 mm
Operating temperature	5 - 40 °C

Cyklop India Private Limited
Regus, Level 13/1331,
Platinum Techno Park
Vashi, Navi
Mumbai
Maharashtra
India 400705

+91 22 61814949 | +91 9820025965
www.cyklop-india.com
partha.das@cyklop-asia.com

